

DUOGUARD CR MOULD RELEASE

GENERAL PURPOSE CONCRETE MOULD RELEASE

CODE: 1528

DUOGUARD CR MOULD RELEASE is a general purpose concrete mould release. Concrete work is normally formed. Hence, we refer to the oil as a release agent suitable for form materials, e.g. steel, wood, plywood, hardboard etc. A release agent is applied to formwork prior to placing concrete against the form. It provides a film at the formwork/concrete interface which facilitates stripping and at the same time minimises blemishes to the concrete surface.

APPLICATION

CR Form Concrete Mould Release is an economical release agent for the manufacture of concrete slabs and pre-stressed concrete

PHYSICAL PROPERTIES

Appearance	Golden
Odour	Bland oily
Density@ 15°C	0.8454
Flash point	>70°C
Kinematic Viscosity at 40°C mm ² /s (cSt)	5.2

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability

STORAGE & HANDLING

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C

SAFETY, HEALTH & ENVIRONMENT

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product. The Safety Data Sheet is available at Sterling Industrial Lubricants website www.sterlinglubricants.com.au or by email: info@sterlinglubricants.com.au.